

The Claims

Sub A2

5

10

15

20

25

30

35

1. A digital signal processing system comprising:
 - a) a signal processor adapted to be connected to a pair of signal transmission paths and through which signal commands on one of the paths are transmitted; and
 - b) a signal canceller operatively associated with the signal processor to subtract undesired signals from received signals on the other of the paths, the signal canceller employing Auxiliary-Vector filtering.

2. The system according to claim 1, wherein the signal canceller contains an array of filter coefficients and wherein the Auxiliary Vector filtering and multiplies the signals by the array of filter coefficients and subtracts the result from the transmitted signal commands.

3. The system according to claim 1, wherein the signal canceller is adaptive in being capable of changing the filter coefficients while receiving data from the transmitted signal commands and from the received signals.

4. The system according to claim 2, wherein the filter coefficients are obtained using the algorithm:

$$\begin{aligned} R &= Y^T * Y \\ V &= Y^T * X \\ G &= (R * V - (V^T * R * V) * V) / \text{norm}(R * V - (V^T * R * V) * V) \\ U &= (G^T * R * V) / (G^T * R * G) \end{aligned}$$

093514-0440

$$w=V-U*G$$

where the vector Y contains N values of the received signal $y[n]$ where N is the number of filter

coefficients, X contains one value $x[n]$ of the

5 transmitted signal commands, G is the Auxiliary Vector, U is a scalar which minimizes output variances of the filter coefficients and w is a vector containing the filter coefficients.

10 5. The system according to claim 1, wherein voice signals are processed.

15 6. The system according to claim 1, wherein the signal processor is the digital signal processor of a voice mail system, and wherein the signal commands include voice mail prompts and the undesired signals include echo.

20 7. A digital signal processing system comprising:
a) a near end and a far end connected by a pair of signal transmission paths;
b) a signal processor at the near end through which signal commands are transmitted from the near end to the far end;
25 c) a signal transducing device at the far end to receive the signal commands and to transmit to the near end signals indicating the state of the signal transducing device; and
30 d) a signal canceller operatively associated with the signal processor to subtract undesired signals from the received

0035454.044401

signals, the signal canceller employing Auxiliary-Vector filtering.

8. The system according to claim 7, wherein the
5 signal canceller contains an array of filter
coefficients and wherein the Auxiliary Vector filtering
takes the signals transmitted from the far end and
multiplies the transmitted signals by the array of
filter coefficients and subtracts the result from the
10 signal commands transmitted from the near end.

9. The system according to claim 1, wherein the
signal canceller is adaptive in being capable of
changing the filter coefficients while receiving data
15 from the signal commands transmitted from the near end
and the signals transmitted from the far end.

10. The system according to claim 8, wherein the
20 filter coefficients are obtained using the algorithm:

$$R=Y^T*Y$$
$$V=Y^T*X$$
$$G=(R*V-(V^T*R*V)*V)/\text{norm}(R*V-(V^T*R*V)*V)$$
$$25 \quad U=(G^T*R*V)/(G^T*R*G)$$
$$w=V-U*G$$

where the vector Y contains N values of the received
signal y[n] where N is the number of filter
30 coefficients, X contains one value x[n] of the
transmitted signal commands, G is the Auxiliary Vector,
U is a scalar which minimizes output variances of the
filter coefficients and w is a vector containing the
filter coefficients.

FOI b7D b7C b7E b7F b7G b7H b7I b7J b7K b7L b7M b7N b7O b7P b7Q b7R b7S b7T b7U b7V b7W b7X b7Y b7Z

11. The system according to claim 7, wherein voice signals are processed.

12. The system according to claim 7, wherein the signal processor is the digital signal processor of a voice mail system, the signal transducing device is a telephone set, wherein the signal commands include voice mail prompts and the undesired signals include echo.

13. A digital signal processing method comprising:

- a) transmitting signal commands from a near end including a signal processor over a first signal path to a far end including a signal transducing device;
- b) receiving over a second signal path from the far end to the near end signals indicating the state of the signal transducing device; and
- c) cancelling undesired signals from the signals received at the near end utilizing a signal canceller employing Auxiliary-Vector filtering.

14. The method according to claim 7, wherein the signal cancelling includes providing an array of filter coefficients and wherein the Auxiliary Vector filtering takes the signals transmitted from the far end and multiplies the transmitted signals by the array of filter coefficients and subtracts the result from the signal commands transmitted from the near end.

15. The method according to claim 7, wherein the signal cancelling is adaptive in being capable of

FOIb0-1515860

changing the filter coefficients while receiving data from the signal commands transmitted from the near end and the signals transmitted from the far end.

- 5 16. The method according to claim 14, wherein the filter coefficients are obtained using the algorithm:

$$\begin{aligned} R &= Y^T * Y \\ V &= Y^T * X \\ 10 \quad G &= (R * V - (V^T * R * V) * V) / \text{norm}(R * V - (V^T * R * V) * V) \\ U &= (G^T * R * V) / (G^T * R * G) \\ w &= V - U * G \end{aligned}$$

where the vector Y contains N values of the received
15 signal y[n] where N is the number of filter coefficients, X contains one value x[n] of the transmitted signal commands, G is the Auxiliary Vector, U is a scalar which minimizes output variances of the filter coefficients and w is a vector containing the
20 filter coefficients.

17. The method according to claim 7, wherein voice signals are processed.

- 25 18. The method according to claim 7, wherein the signal processor is the digital signal processor of a voice mail system, the signal transducing device is a telephone set, wherein the signal commands include voice mail prompts and the undesired signals include echo.

- 30 19. A program storage device readable by a machine embodying a program of instructions executable by the machine for signal processing in which undesired signals are cancelled, the instructions comprising:

35

09835154.041401

- 0935154-041401
- a) transmitting signal commands from a near end including a signal processor over a first signal path to a far end including a signal transducing device;
 - 5 b) receiving over a second signal path from the far end to the near end signals indicating the state of the signal transducing device; and
 - 10 c) cancelling undesired signals from the signals received at the near end utilizing a signal canceller employing Auxiliary-Vector filtering.

20. The program storage device according to claim 15 19, wherein the signal cancelling includes providing an array of filter coefficients and wherein the Auxiliary Vector filtering takes the signals transmitted from the far end and multiplies the transmitted signals by the array of filter coefficients and subtracts the result 20 from the signal commands transmitted from the near end.

21. The program storage device according to claim 19, wherein the signal cancelling is adaptive in being capable of changing the filter coefficients while 25 receiving data from the signal commands transmitted from the near end and the signals transmitted from the far end.

22. The program storage device according to claim 30 20, wherein the filter coefficients are obtained using the algorithm:

$$\begin{aligned} R &= Y^T * Y \\ V &= Y^T * X \\ 35 \quad G &= (R * V - (V^T * R * V) * V) / \text{norm}(R * V - (V^T * R * V) * V) \end{aligned}$$

$$U = (G^T * R * V) / (G^T * R * G)$$
$$w = V - U * G$$

where the vector Y contains N values of the received
5 signal y[n] where N is the number of filter
coefficients, X contains one value x[n] of the
transmitted signal commands, G is the Auxiliary Vector,
U is a scalar which minimizes output variances of the
filter coefficients and w is a vector containing the
10 filter coefficients.

23. The program storage device according to claim
19, wherein voice signals are processed.

15 24. The program storage device according to claim
19, wherein the signal processor is the digital signal
processor of a voice mail system, the signal transducing
device is a telephone set, wherein the signal commands
include voice mail prompts and the undesired signals
20 include echo.

0933154 04401